

Grain Handling Group

Jason Beuligmann Thomas Sprague

April 15th, 2005

Objective:

- Design the grain handling setup for an Insight yield monitor system,
- Construct the grain handling components; and
- Test and demonstrate the grain handling system.

The following will be completed:

1) Design

- a. Tank and frame design requirements
- b. Casters and conveyer

2) Construction


- a. Location
- b. Tank and frame construction



This purpose of this project is to determine the accuracy of the insight yield monitor and demonstrate the calibration of a yield monitor in a class room setting.


Objective 1a. Tank and frame design requirements

- Tanks must be able to hold 10 bushel
- Tank and frame must be portable
- Must be 32 inches wide to fit through any standard door
- Must be strong enough to support 1,000 pounds
- The first tank must be able to weigh the grain.



Gravity Wagon Grain Volume

<http://grapevine.abe.msstate.edu/~fto/tools/vol/gravitywagon.html>



AutoCAD drawing of tanks

Objective 1b. Casters, Scales, and Conveyor

- Casters were purchased from Northern Tool company
- Scales and conveyor were purchased from Nichols Electronics Company
- Scales has a 3,000 lb max with Digital screen
- Conveyor can handle over 10 bushel/minute




Rubber casters were used for several reasons:

- 1) To obtain the needed height of the carts
- 2) Easy to push even when fully loaded
- 3) Parking brakes for when in use



Mount Length	Capacity	Part #	Description
33 1/2"	3,300 lbs.	400144	Stock Weigh 3300-33 1/2" Load Cell and Mount

- Are self-aligning on uneven terrain
- Are more conducive to shock absorption via patented rubber mounts
- Handle the stress of shock loads in most animal weighing procedures
- Improve weighing reliability on all surfaces
- Provide increased stability due to wider mounts





Objective 2a. Construction Location

- 1) Built at Beuligmann Farms
- 2) All of the steel was bought and cut at Nix Welding shop
- 3) Welded together by Jason and Thomas
- 4) Painted by John Beuligmann

Objective 2b. Tank and Frame Construction

- 1) The tank was built out of 12 gauge steel
- 2) The frame was constructed out of 2" x 2" tubing
- 3) 1.5" angle iron connects the tank to the frame
- 4) Casters are bolted to the bottom of the frame
- 5) Sliding doors are on the front of both tanks



We built a wood mockup to make sure our design was adequate.



Special thanks to:

Nichols Electronic Company Beuligmann Farms
Nix Welding Prof. Gaines Miles

PURDUE
UNIVERSITY

Grain Handling Group Jason Beuligmann
Thomas Sprague ASM April 15th, 2005

