PURDUE UNIVERSITY

Justin G. Lewton (Agricultural Systems Management)

Background & Objective:

The objective of this project was to create a proof of concept design, to add a Seed Lock wheel, also known as a firming wheel, to a Case IH, 500 series air seeder row unit. The reason for this is that in arid areas seed to soil contact is critical for a crop to have the best chance at a healthy start. The seed is able to pull more moisture out of the surrounding soil, creating more even germination. This influences the crop throughout its life span until harvest, where a greater yield can be attained, due to the crop receiving a better start. This project is geared toward creating an after-market option that is easily attachable and will both provide the farmer with a better option than buying a new machine, as well as creating, and developing markets for Case IH.

Budget:

Material	Aquisition	Сс	st/Val
Case IH 500 series Row Unit	Provided	\$	1,800.0
1/2" Flat Iron	On Hand	\$	18.2
3/4" Round Stock	On Hand	\$	7.
3/4" I.D. Pipe	On Hand	\$	6.2
Seed Lock Wheel	Provided	\$	-
1-1/4" Bearing	Purchased	\$	6.
1/4" Linch Pin	Purchased	\$	1.2
1/2" Carriage Bolt	Purchased	\$	0.4
Paint	Purchased	\$	7.9
Machining/Fitting	156 Hours	\$	10.0
Total Value of Project		\$	3, <mark>408.</mark> 4
Total Cost of Project w/ Labor		\$	1, <mark>608.</mark> 4
Total Cost of Project w/o Labor		\$	48.4

Timeline:

Spring 2016 Schedule	Seed Lock Wheel					
	Weeks 1-3	Weeks 4-6	Weeks 7-9	Weeks 10-12	Weeks 13-16	
Order Materials						
Measurements/Design						
Fabrication						
Mock-up/Fabrication						
Troubleshooting						
Final Assembly/Report						

Sponsor: Kevin Richman – Case IH

Technical Advisor: Dharmendra Saraswat, Ph. D.

CAPSTONE/DESIGN EXPERIENCE 2016 Seed Lock Wheel

Constraints:

Space inside of row unit ✤ No alterations to row unit The goal of this project was to create an after market product that a farmer could buy and bolt onto his current machine, without hours of machine work, or alterations to Case IH's design.

- Simple bolt on part for farmer Adjustable down Pressure
- Quick release for wet
- conditions

Instructors: Robert Stwalley, Ph. D., PE Bernard Engel, Ph. D., PE

Acknowledgements: A special thank you to Mr. Scott Brand, and Mr. Daniel Skelton for the machining, and modeling assistance. Also, I would like to thank Mr. Scott Snider for all of his help.

Global Impact & Sustainability:

With the ever growing population, it is critical for farmers around the world to be as efficient, and as productive as possible no matter the growing conditions. This design can help increase productivity of farmers attempting to grow crops in semi-arid conditions, thus helping feed the population.

Wheat is a prime example:

Impact of Gre

Loaves of bread / B Loaves of bread Co **2014 Harvested Acr 2014 Average Yield 2014 Total Producti Increase in Product Increase in Average Increase in Total Pro Increase in loaves o Possible additional**

Final Solution:

Mounted Draw-Bar Arm

- Same mounting holes as the opener, for easy attachment.
- Angle is corrected through an angled hole
- Stops to keep the trailing arm from hitting opener when machine is lifted.
- Pipe for the shaft pivot.
- Contoured shape for tight fit, and to shed straw and other material.





Trailing Arm

- Hardened steel pivot shaft, with a hole for a linchpin for quick detachment.
- slide past.
- pressure
- Custom Seed-Lock wheel of 7" in diameter, and only 0.5" wide to fit inside constraints, as well as fit inside furrow.

PURDUE AGRICULTURE PURDUE UNIVERSITY



ater Wheat Production on Global Food Supply*					
ushel of Wheat	73				
nsumed per capita (U.S.) per year	53				
es	46,381,000				
(bu/ac)	44				
on (bu)	2,026,849,700				
ion (%)	1%				
e Yield (bu/ac)	0.219				
oduction (bu/ac)	10,134,249				
of bread	739,800,141				
people fed per year	13,958,493				





- Countersunk carriage bolt for smooth surface for spring to
- 3 Different spring tension settings for variable down



Purdue University is an equal opportunity/equal access institution.